
Pelsan

Brief Catalogue 2024-25

Indoor Luminaires

Outdoor Luminaires

Industrial Luminaires



41 bright years

Pelsan

Since 1982

More than 3500 SKU's


500 Employees

5 million luminaires production capacity per year



Factory

- Electronic Assembly Line
- Plastic Injection Moulding Area
- Semi-finished Goods Process Area
- Moulding Area
- Diffuser Treatment Area



- Landscape Lighting Fixture Parts Manufacturing Area
- Glass Reinforced Plastic (GRP) Product Manufacturing Area
- Powder Coating & Painting Area
- Assembly Line
- Offices

30000 m² Manufacturing Zone

R&D Center
15 Engineers

Accredited
Laboratory
23 standards

Load / Unload
10 Trucks



Pelsan

WE DESIGN LUMINAIRES

MECHANICAL DESIGN

OPTICAL DESIGN



THERMAL DESIGN

ELECTRICAL DESIGN

08 Recessed Mounted Backlight Office Luminaires




09 Surface Mounted Backlight Office Luminaires



12 Recessed and Surface Mounted Office Luminaires



13 Sterile Environment and Hospital Luminaires



14 Recessed Mounted Office Luminaires



15 Linear Luminaires



17 Downlight Luminaires



21 Ceiling Luminaires



23 Sensors



24 Super Market Luminaires



25 Batten Luminaires



26 GRP Waterproof Luminaires



29 Aluminium Waterproof Luminaires



30 PC Waterproof Luminaires



Index

34 Emergency Luminaires



37 Canopy Luminaires



38 Highbay Luminaires



43 Ex-Proof Luminaires



46 Floodlights



51 Road and Street Luminaires



54 Solar Street Lighting Luminaires



56 Park and Garden Luminaires



64 Bollards



66 Appliques



68 Garden and Wallwasher Luminaires



70 LED Tube



71 Certificates



Isoled G3T

Up to 126lm/W



Up to +126lm/W | European Origin ENEC Driver | LM80-TM21 Reports | PMMA Diffuser | PF >0,95



Isoled 60x60 Recessed Mounted


111412 | 36 W | 4464lm | 124lm/W | 595x595x61 mm | 580x580 | 6pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option

3000K | 4000K | 6500K | Plaster Ceiling - Clip-in

TSE EAC CE 5 YEARS WARRANTY



Isoled 30x30 Recessed Mounted


111343 | 12 W | 1416lm | 118lm/W | 295x295x61 mm | 280x280 | 5pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option

3000K | 4000K | 6500K | Plaster Ceiling - Clip-in

TSE EAC CE 5 YEARS WARRANTY



Isoled 30x60 Recessed Mounted

111462 | 17 W | 2143lm | 126lm/W | 295x595x61 mm | 270x570 | 5pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option

3000K | 4000K | 6500K | Plaster Ceiling - Clip-in

TSE EAC CE 5 YEARS WARRANTY



Isoled 30x120 Recessed Mounted

111465 | 36 W | 4464lm | 124lm/W | 295x1195x61 mm | 280x1180 | 4pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option

3000K | 4000K | 6500K | Plaster Ceiling - Clip-in

TSE EAC CE 5 YEARS WARRANTY

Pelsan

Dekoled G3T

Up to 126lm/W



Up to +126lm/W | European Origin ENEC Driver | LM80-TM21 Reports | PMMA Diffuser | PF >0,95



Dekoled 60x60 Surface Mounted

111440 | 36 W | 4464lm | 124lm/W | 600x600x61 mm | 6pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

UGR Option

3000K | 4000K | 6500K

TSE EAC CE 5 YEARS WARRANTY



Dekoled 30x30 Surface Mounted

111358 | 12 W | 1416lm | 118lm/W | 300x300x61 mm | 5pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

UGR Option

3000K | 4000K | 6500K

TSE EAC CE 5 YEARS WARRANTY



Dekoled 30x60 Surface Mounted

111456 | 17 W | 2142lm | 126lm/W | 300x600x61 mm | 5pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

UGR Option

3000K | 4000K | 6500K

TSE EAC CE 5 YEARS WARRANTY



Dekoled 30x120 Surface Mounted

111459 | 36 W | 4464lm | 124lm/W | 300x1200x61 mm | 4pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

UGR Option

3000K | 4000K | 6500K

TSE EAC CE 5 YEARS WARRANTY

Isoled G3L



100lm/W | ENEC Certified Driver | LM80-TM21 Reports | LED Module with PMMA Lens




Isoled 60x60 Recessed Mounted

111475 | 36 W | 3708lm | 103lm/W | 595x595x40 mm | 580x580 | 6pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option | 3000K | 4000K | 6500K | Plaster Ceiling - Clip-in




Isoled 30x60 Recessed Mounted

111822 | 17 W | 1700lm | 100lm/W | 295x595x40 mm | 280x580 | 6pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option | 3000K | 4000K | 6500K | Plaster Ceiling - Clip-in



Isoled 30x120 Recessed Mounted

113009 | 36 W | 3708lm | 103lm/W | 295x1115x40 mm | 1180x280 | 4pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option | 3000K | 4000K | 6500K | Plaster Ceiling - Clip-in



Isoled 60x120 Recessed Mounted

113247 | 72 W | 7416 | 103lm/W | 1195x595x45 mm | 1180x580 | 1pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option | 3000K | 4000K | 6500K | Plaster Ceiling - Clip-in

Dekoled G3L



100lm/W | ENEC Certified Driver | LM80-TM21 Reports | LED Module with PMMA Lens



Dekoled 60x60 Surface Mounted

111500 | 36 W | 3708lm | 103lm/W | 600x600x61 mm | 6pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option | 3000K | 4000K | 6500K



Dekoled 30x60 Surface Mounted

111840 | 17 W | 1700lm | 100lm/W | 300x600x61 mm | 5pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option | 3000K | 4000K | 6500K



Dekoled 30x120 Surface Mounted

113042 | 36 W | 3708lm | 103lm/W | 300x1200x61 mm | 4pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option | 3000K | 4000K | 6500K



Dekoled 60x120 Surface Mounted

113354 | 36 W | 3708lm | 103lm/W | 1200x600x61 mm | 1pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

UGR Option | 3000K | 4000K | 6500K





Energy Efficient, +130lm/W

- Daylight and Motion Sensor Option
- +130lm/W Efficacy
- Surface Mounted Option

Effica Recessed Mounted / Surface Mounted

108988 | 35 W | 4550lm | 130lm/W | 595x595x82 mm | 575x575 | 1pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

3000K | 4000K | 6500K | Plaster Ceiling - Clip-in | UGR Option



Energy Efficient, Up to 145lm/W

- Anti-Glare Design, UGR<19
- CRI90 Option
- Surface Mounted, Clip-in Option

Fertis Recessed Mounted / Surface Mounted

115460 | 35 W | 5075lm | 145lm/W | 595x595x33 mm | 570x570 | 10pcs

Metal | OPAL Diffuser | ENEC Driver | IP40 | DALI Option | Emergency unit



Visual Comfort! UGR<19

- Anti-Glare Design, UGR<19
- +100lm/W Efficacy
- Aluminium Reflector

Retto Recessed Mounted / Surface Mounted

110748 | 36 W | 3600lm | 100lm/W | 595x595x40 mm | 575x575 | 6pcs

Metal | OPAL Diffuser | Aluminium Reflector | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

Plaster Ceiling - Clip-in | cm Dimension Option: 30x120 - 30x150

3000K | 4000K | 6500K





Indirect Light, UGR<16

- Direct and Indirect Light
- Anti-Glare Design
- Aesthetic Design

Divaled Indirect

Recessed Mounted / Surface Mounted

108408 | 42 W | 2920lm | 70lm/W | 595x595x75 mm | 580x580 | 4pcs

Metal | OPAL Diffuser | Indirect Light | LM80 TM21 | ENEC Driver | IP20 | DALI Option | Emergency unit

3000K | 4000K | 6500K | Clip-in

Quick and easy installation



Sterile UGR<19 Recessed Mounted

110608	36 W	3240lm	600x600x50 mm	2pcs

Metal | Tempered Glass | LM80 TM21 | ENEC Driver | IP65 | DALI Option | Emergency unit

3000K | 4000K | 6500K

CE



Sterile IP65 Recessed Mounted

109777	36 W	3240lm	599x595x80 mm	575x575	2pcs

Metal | Tempered Glass | LM80 TM21 | ENEC Driver | IP65 | DALI Option | Emergency unit

3000K | 4000K | 6500K

Plaster Ceiling

Dimension Options: 30x30 - 30x60 -30x120

CE



Clealed IP65 Recessed Mounted

111518	12 W	1416lm	118lm/W	295x295x61 mm	280x280	5 pcs
111542	36 W	4464lm	124lm/W	595x595x61 mm	580x580	6 pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65 | DALI Option | Emergency unit

3000K | 4000K | 6500K

TSE EAC CE



Sterile IP65

109906	36 W	2880lm	600x600x75 mm	2 pcs

Metal | Tempered Glass | LM80 TM21 | ENEC Driver | IP65 | DALI Option | Emergency unit

3000K | 4000K | 6500K

Surface Mounted Option

Dimension Options: 30x30 - 30x60 -30x120

CE



Negatoscope Surface Mounted


106101	42 W	4620lm	600x600x50 mm	1pcs
106103	84 W	9240lm	1200x600x50 mm	1pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP20 | Emergency unit

4000K | 6500K

CE

Maximum Visual Comfort





Anti-Glare
Optic Design



30x30
113783



60x60
113787


Nora G2 **UGR<19**

113783	12 W	1500lm	125lm/W	295x295x35 mm	270x270	4pcs
113787	36 W	4500lm	125lm/W	595x595x35 mm	570x570	5pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

3000K 4000K 6500K Plaster Ceiling - Clip-in

UGR (Unified Glare Rating)



TSE EAC CE



30x30
113785



60x60
113789


Nora G2 **UGR<16**

113785	12 W	1260lm	105lm/W	295x295x35 mm	270x270	4pcs
113789	36 W	4068lm	113lm/W	595x595x35 mm	570x570	5pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

3000K 4000K 6500K Plaster Ceiling - Clip-in

UGR (Unified Glare Rating)




TSE EAC CE

Pelsan

Maximum Visual Comfort



Anti-Glare
Optic Design




Nora Linear **UGR<19**

110674	14 W	1330lm	580x58x85 mm	1pcs
110676	20 W	1900lm	865x58x85 mm	1pcs
110678	28 W	2660lm	1150x58x85 mm	1pcs
110681	42 W	3990lm	1435x58x85 mm	1pcs


Aluminium | IP40 | DALI Option | Emergency unit | OPAL Diffuser

ENEC Driver | LM80 TM21 | 3000K | 4000K | 6500K

Mounting Options



UGR (Unified Glare Rating)



TSE EAC CE




Nora Linear **UGR<16**

110673	14 W	728lm	580x58x85 mm	1pcs
110675	20 W	1040lm	865x58x85 mm	1pcs
110677	28 W	1456lm	1150x58x85 mm	1pcs
110680	42 W	2184lm	1435x58x85 mm	1pcs


Aluminium | IP40 | DALI Option | Emergency unit | OPAL Diffuser

ENEC Driver | LM80 TM21 | 3000K | 4000K | 6500K

Mounting Options



UGR (Unified Glare Rating)



TSE EAC CE



Continuous Linear Connection

Continuous Linear Connection
with External Connection aparatus
without opening the product.


Eterna G2 Surface Mounted (57mm)

114415	14 W	1512lm	108lm/W	620x57x85 mm	1pcs
114416	20 W	2200lm	110lm/W	900x57x85 mm	1pcs
114417	28 W	3024lm	108lm/W	1220x57x85 mm	1pcs
114418	42 W	4494lm	107lm/W	1500x57x85 mm	1pcs

Mounting Options



Continuous Linear Connection



Aluminium · IP40 · DALI Option · Emergency unit · OPAL Diffuser · Aluminium Reflector
ENEC Driver · LM80 TM21 · 3000K · 4000K · 6500K

TSE EAC CE 5 YEARS WARRANTY



Linear Indirect Light



Eterna Indirect Surface Mounted (47mm)

206015	42 W	2600-1600lm	100lm/W	900x47x68 mm	1pcs
206016	52 W	3400-1800lm	100lm/W	1200x47x68 mm	1pcs
206017	68 W	4400-2400lm	100lm/W	1470x47x68 mm	1pcs
206018	100 W	6000-4000lm	100lm/W	2000x47x68 mm	1pcs

Aluminium · IP40 · DALI Option · Emergency unit · OPAL Diffuser · ENEC Driver · LM80 TM21
3000K · 4000K · 6500K

TSE EAC CE 5 YEARS WARRANTY



Eterna G2 Recessed Mounted (77mm)

114419	14 W	1512lm	108lm/W	625x77x85 mm	1pcs
114420	20 W	2200lm	110lm/W	895x77x85 mm	1pcs
114421	28 W	3024lm	108lm/W	1225x77x85 mm	1pcs
114422	42 W	4494lm	107lm/W	1505x77x85 mm	1pcs

Aluminium · IP40 · DALI Option · Emergency unit · OPAL Diffuser · Aluminium Reflector
ENEC Driver · LM80 TM21 · 3000K · 4000K · 6500K

Mounting Options



TSE EAC CE 5 YEARS WARRANTY




Trenta G2

113031	36 W	3060lm	85lm/W	1020x33x60 mm	12pcs

Aluminium · IP40 · DALI Option · Emergency unit · OPAL Diffuser · Aluminium Reflector
ENEC Driver · LM80 TM21 · 3000K · 4000K · 6500K

Mounting Options



CE

Backlight LED Downlight Luminaires


Pelsan



There is always a Tira suitable to your place!

- +50.000 hours lifetime
- DALI Dim Options
- Black and White Frame

3 Different Body Options





Tira G2 4"

114130 | 12 W | 1200lm | 100lm/W | 145x30 mm | 120 | 30pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

3000K 4000K 6500K

TSE CE 5 YEARS WARRANTY



Tira G2 6"

114134 | 24 W | 2400lm | 100lm/W | 180x30 mm | 152 | 20pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

3000K 4000K 6500K

TSE CE 5 YEARS WARRANTY



Rina 4" Surface Mounted

110599 | 12 W | 1200lm | 100lm/W | 130x100 mm | 20pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

3000K 4000K 6500K

TSE CE 5 YEARS WARRANTY



Rina 6" Surface Mounted

110600 | 24 W | 2472lm | 103lm/W | 175x100 mm | 16pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

3000K 4000K 6500K

TSE CE 5 YEARS WARRANTY





Black frame option

Tira Round

106928	5 W	550lm	110lm/W	148x56,5 mm	132	20pcs
106934	7 W	770lm	110lm/W	148x56,5 mm	132	20pcs
106937	10 W	1100lm	110lm/W	148x56,5 mm	132	20pcs
106943	10 W	1100lm	110lm/W	197x56,5 mm	185	15pcs
106950	15 W	1545lm	103lm/W	197x56,5 mm	185	15pcs
106961	20 W	2000lm	100lm/W	197x56,5 mm	185	15pcs
106969	20 W	2000lm	100lm/W	240x56,5 mm	220	10pcs
106977	25 W	2500lm	100lm/W	240x56,5 mm	220	10pcs
106985	35 W	3325lm	95lm/W	240x56,5 mm	220	10pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

3000K 4000K 6500K





Black frame option

Tira Square

106991	5 W	550lm	110lm/W	148x148x56,5 mm	132	20pcs
106994	7 W	770lm	110lm/W	148x148x56,5 mm	132	20pcs
106997	10 W	1100lm	110lm/W	148x148x56,5 mm	132	20pcs
107003	10 W	1100lm	110lm/W	197x197x56,5 mm	185	15pcs
107006	15 W	1545lm	103lm/W	197x197x56,5 mm	185	15pcs
107012	20 W	2000lm	100lm/W	197x197x56,5 mm	185	15pcs
107018	20 W	2000lm	100lm/W	233x233x56,5 mm	220	10pcs
107021	25 W	2500lm	100lm/W	233x233x56,5 mm	220	10pcs
107025	35 W	3325lm	95lm/W	233x233x56,5 mm	220	10pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 40 | DALI Option | Emergency unit

3000K 4000K 6500K





Black frame option

Tira IP54

107069	7 W	665lm	95lm/W	148x56,5 mm	132	20pcs
107072	10 W	950lm	95lm/W	148x56,5 mm	132	20pcs
107075	15 W	1545lm	103lm/W	197x56,5 mm	185	15pcs
107078	20 W	2000lm	100lm/W	197x56,5 mm	185	15pcs
107081	25 W	2500lm	100lm/W	233x56,5 mm	220	10pcs
107084	35 W	3325lm	95lm/W	233x56,5 mm	220	10pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP 54 | DALI Option | Emergency unit

3000K 4000K 6500K

Slim Backlight LED Downlight Luminaires

Pelsan

Dore

5 YEARS WARRANTY



Slim Design

Up to 134lm/W High Efficiency

ENEC Certificated Driver

+50.000h Lifetime



Dore 4"

110864	7 W	791lm	113 lm/W	120x45 mm	105	30pcs

ABS | OPAL Diffuser | LM80 TM21 | IP40 | Emergency unit | DALI Option

3000K 4000K 6500K



Dore 6"

110865	10 W	1120lm	112 lm/W	170x45 mm	155	30pcs
110866	13 W	1547lm	119 lm/W	170x45 mm	155	30pcs

ABS | OPAL Diffuser | LM80 TM21 | IP40 | Emergency unit | DALI Option

3000K 4000K 6500K



Dore 8"

110867	18 W	2412lm	130 lm/W	225x45 mm	205	20pcs
110868	22 W	2948lm	134 lm/W	225x45 mm	205	20pcs

ABS | OPAL Diffuser | LM80 TM21 | IP40 | Emergency unit | DALI Option

3000K 4000K 6500K



Dore Surface Mounted

111752	18 W	2412lm	134 lm/W	228x55 mm	10pcs
111755	22 W	2420lm	110 lm/W	228x55 mm	10pcs

ABS | OPAL Diffuser | LM80 TM21 | IP40 | Emergency unit | DALI Option

3000K 4000K 6500K

Sirma



Slim Design
Backlight Light Comfort
Internal Driver
Emergency Unit Option



Sirma 6W/9W

110331	6 W	534lm	89 lm/W	120x45 mm	105	20pcs
110334	9 W	792lm	88 lm/W	120x45 mm	105	20pcs

ABS | OPAL Diffuser | LM80 TM21 | IP40 | Emergency unit

3000K 4000K 6500K



Sirma 12W/15W

110341	12 W	1128lm	94 lm/W	170x45 mm	155	15pcs
110344	15 W	1365lm	91 lm/W	170x45 mm	155	15pcs

ABS | OPAL Diffuser | LM80 TM21 | IP40 | Emergency unit

3000K 4000K 6500K



Sirma 18W

110350	18 W	1872lm	104 lm/W	225x45 mm	205	10pcs

ABS | OPAL Diffuser | LM80 TM21 | IP40 | Emergency unit

3000K 4000K 6500K



Sirma Surface Mounted

111749	18 W	1782lm	99 lm/W	228x55 mm		10pcs

ABS | OPAL Diffuser | LM80 TM21 | IP40 | Emergency unit

3000K 4000K 6500K



206677 206913 208414

Pio Surface Mounted

206677	12 W	840lm	6500K	Ø258x57 mm	10pcs
206913	18 W	1260lm	6500K	Ø335x60 mm	10pcs
208414	28 W	1960lm	6500K	Ø387x58 mm	10pcs

Metal | OPAL Diffuser | IP40

6500K

CE



111309 111306

Punto Surface Mounted

111306	24 W	720lm	6500K	350x74x350 mm	10pcs
111309	24 W	720lm	6500K	350x74 mm	10pcs

Metal | OPAL Diffuser | IP40 | SENSOR Option

6500K

CE



111314 111312

Picto Surface Mounted

111312	24 W	1920lm	350x74x350 mm	10pcs
111314	24 W	1920lm	350x74 mm	10pcs

Metal | OPAL Diffuser | IP40

6500K

CE



Sense Surface Mounted

104359	2xE27 Sensor	2xE27	–	300x105 mm	10pcs
110697	2xE27 Emergency Sensor	2xE27	–	300x105 mm	10pcs
110695	2xE27	2xE27	–	300x105 mm	10pcs
110696	LED Sensor	8 W	864lm	300x105 mm	10pcs
104369	Emergency LED Sensor	8 W	740lm	300x105 mm	10pcs

Metal | SEMI OPAL Diffuser | IP20

4000K 6500K

CE



Oval Bulkhead

204487	E27	210x110x92 mm	18pcs

Aluminium injection | Tempered Glass

IP54

CE

Havana

Screwless Design Easy Installation




Easy Installation

EMG + Microwave Sensor

IP66 Dust and Waterproof

WHITE
GRAY
BLACK



IP66

Dust and Waterproof

Havana E27 Lampholder


111193	1XE27	max 20 W	260x87 mm	8pcs
111194	2XE27	max 20 W	260x87 mm	8pcs
111221	1XE27 + Sensor	max 20 W	260x87 mm	8pcs
111223	2XE27 + Sensor	max 20 W	260x87 mm	8pcs

Polymer Injection Body | OPAL Diffuser | IP66

3000K 4000K 6500K

EAC CE

WHITE
GRAY
BLACK



IP66

Dust and Waterproof

Havana (LED+ENEC Driver)


111226	LED	15 W	1605lm	260x87 mm	8pcs
111236	LED+Sensor	15 W	1605lm	260x87 mm	8pcs
111245	LED+Emergency	15 W	1605lm	260x87 mm	8pcs
111260	LED+Emergency+Sensor	15 W	1605lm	260x87 mm	8pcs

Polymer Injection Body | OPAL Diffuser | LM80 TM21 | ENEC Driver | Emergency unit | IP66

3000K 4000K 6500K

EAC CE

WHITE
GRAY
BLACK



IP66

Dust and Waterproof

Havana Integrated Driver

111692	LED	18 W	1530lm	260x87 mm	8pcs
111701	LED + Sensor	18 W	1530lm	260x87 mm	8pcs

Polymer Injection Body | OPAL Diffuser | LM80 TM21 | IP66

3000K 4000K 6500K


EAC CE



360° Motion Sensor

314720 | 80x41 mm | 50pcs

RoHS IP20






Presence Sensor

314733 | 102,5x58,3 mm | 50pcs

RoHS IP20






Microwave Sensor

314725 | 54,5x39,5x25 mm | 100pcs

RoHS IP20






Recessed Mounted Sensor

314726 | 75,7x77 mm | 60 ° | 50pcs

RoHS IP20




New



Recessed Mounted Microwave Sensor

326838 | mm | 66 ° | 50pcs

RoHS




New



Surface Mounted Microwave Sensor

326839 | mm | ° | 50pcs

RoHS






180° Motion Sensor

314717 | 110x66x135 mm | 50pcs

RoHS IP20






Four Way Motion Sensor

314729 | 58,8x72,3 mm | 50pcs

RoHS IP20






IP65 Sensor Box

314735 | 134x66 mm | 50pcs

RoHS IP65

Protects indoor (IP65) sensors from rain and dust.



Multiline

Monoline





120lm/W Efficacy!

- Energy Saving up to %60
- Easy Linear Connection
- x2.5 Times Longer Life to T5 Fluorescent

Monoline


109563	28 W	120lm/W	1133x169x72 mm	6pcs
109565	35 W	120lm/W	1415x169x72 mm	4pcs

Metal | OPAL Diffuser | Aluminium Reflector | LM80 TM21 | ENEC Driver | IP40 | DALI Option | Emergency unit

3000K 4000K 6500K

CE





114lm/W Efficacy!

- Directs the Light to the Desired Spot
- 7 Step angle light level, from 15° to 115°
- Provides Continuous Linear Light

Multiline

105381	35 W	4020lm	114lm/W	1200x140x58 mm	4pcs
105383	35 W	4020lm	114lm/W	1500x140x58 mm	4pcs
105385	50 W	5720lm	114lm/W	1500x140x58 mm	4pcs

Metal | OPAL Diffuser | Aluminium Reflector | Clear & Frosted Diffuser | LM80 TM21 | ENEC Driver

3000K 4000K 6500K | IP40 | DALI Option | Emergency unit

CE



IP65 Linea
Polymer Injection Body

113655	36 W	3600lm	100lm/W	1133x75x25 mm	20pcs

Polymer Inj. Body | IP65 | 6500K

CE




IP40 Linea
Polymer Injection Body

113653	36 W	3060lm	90lm/W	1115x75x25 mm	20pcs

Polymer Inj. Body | IP40 | 6500K

CE




IP65 LED Tube Batten
Polyester Body

103200	1xG13	1270x130x68 mm	6pcs
103261	1xG13	1560x130x68 mm	6pcs

GRP | G13 | IP65

Options X2 LED Tube

CE




IP54 LED Tube Batten
Metal Body

111276	1xG13	640x55x90 mm	12pcs
111618	1xG13	1260x55x90 mm	12pcs
111620	1xG13	1560x55x90 mm	12pcs

Metal | G13 | IP54

Options X2 LED Tube

CE



IP20 LED Tube Batten
Metal Body

111621	1xG13	1200x40x54 mm	1pcs
111279	1xG13	600x40x54 mm	1pcs

Metal | G13 | IP20

Options X2 LED Tube

CE




Wide Product Range

- LED / LED Tube / TLD
- Exproof / Frozen / Carpark
- Anti-Corrosion GRP Body
- 60cm / 120cm / 150cm
- Opal / Semi-Opal / Clear Diffuser
- Stainless Steel / Polymer / Anti-vandal latch
- DALI / Casambi / Emergency Options


Largo LED


Largo Max


Largo LED Tube


Largo LED Tube



Largo LED

109150	20 W	2400 lm	120lm/W	663x85x85 mm	6pcs
109151	36 W	4500 lm	125lm/W	1275x85x85 mm	6pcs
109153	42 W	5040 lm	120lm/W	1573x85x85 mm	6pcs
111114	50 W	6750 lm	135lm/W	1275x125x85 mm	6pcs
111113	75 W	9600 lm	128lm/W	1275x125x85 mm	6pcs

GRP · OPAL Diffuser · CLEAR Diffuser · SEMI OPAL Diffuser · LM80 TM21 · ENEC Driver · IP65

DALI Option · 1-10V · Emergency unit · CASAMBI

3000K · 4000K · 6500K · Corridor Function

TSE · EAC · CE · 5 YEARS WARRANTY



Largo LED Tube (1xG13)

102669	1xG13	663x85x85 mm	6pcs
102713	1xG13	1275x85x85 mm	6pcs
102867	1xG13	1573x85x85 mm	6pcs

GRP · CLEAR Diffuser · IP65 · G13 · Emergency unit

EAC · CE



Largo LED Tube (2xG13)

102687	2xG13	663x85x125 mm	6pcs
102744	2xG13	1273x85x125 mm	6pcs
102878	2xG13	1573x85x125 mm	4pcs

GRP · CLEAR Diffuser · IP65 · G13 · Emergency unit

EAC · CE

Pelsan





Largo Max

111114	50 W	6750 lm	135 lm/W	1275x125x85 mm	6pcs
111113	75 W	9600 lm	128 lm/W	1275x125x85 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | SEMI OPAL Diffuser | LM80 TM21 | ENEC Driver

IP65 | Corridor Function

3000K 4000K 6500K

TSE EAC CE



Largo Carpark


113489	36 W	3960lm	1273x85x85 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | SEMI OPAL Diffuser | LM80 TM21 | ENEC Driver

IP65 | Corridor Function

3000K 4000K 6500K

Carpark Function



CE

24V DC



Largo 24V DC

110119	21 W	2100lm	663x85x85 mm	6pcs
110114	42 W	4200lm	1273x85x85 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | SEMI OPAL Diffuser | LM80 TM21 | IP65

3000K 4000K 6500K

CE



Largo LED Ex-Proof Waterproof

108458	25 W	2750 lm	110lm/W	670x85x125 mm	6pcs
108459	45 W	4950 lm	110lm/W	1280x85x125 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K

Ex ZONE 2 ZONE 22 — II 3G Ex nR IIC T6 Gc
II 3D Ex tc IIIC T 80° Dc




Largo T8 Ex-Proof Waterproof

108297	2x18 W	–	G13 TL-D	670x85x125 mm	6pcs
108298	2x36 W	–	G13 TL-D	1280x85x125 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K

Ex ZONE 2 ZONE 22 — II 3G Ex nR IIC T6 Gc
II 3D Ex tc IIIC T 80° Dc



Largo Chemical Resistant

105871	21 W	2100lm	100lm/W	663x85x85 mm	6pcs
105884	42 W	4200lm	100lm/W	1273x90x90 mm	6pcs
105894	63 W	6300lm	100lm/W	1573x85x85 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | SEMI OPAL Diffuser | LM80 TM21 | ENEC Driver

IP65

3000K 4000K 6500K

CE



Suitable for Frozen Storage Fields

Largo Frozen

105871	21 W	2100lm	100lm/W	663x85x85 mm	6pcs
105884	42 W	4200lm	100lm/W	1273x90x90 mm	6pcs
105894	63 W	6300lm	100lm/W	1573x85x85 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | SEMI OPAL Diffuser | LM80 TM21 | ENEC Driver

IP65 | Corridor Function

3000K 4000K 6500K

CE

Aluminium Waterproof Luminaires

Pelsan

5 YEARS WARRANTY





Prota G3

115014	18 W	2250lm	125lm/W	555x64x46 mm	12 pcs
115016	23 W	2921lm	127lm/W	805x64x46 mm	12 pcs
115018	33 W	4125lm	125lm/W	1055x64x46 mm	12 pcs
115020	43 W	5504lm	128lm/W	1305x64x46 mm	12 pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65 | DALI Option | Emergency unit

3000K 4000K 6500K

TSE EAC CE 5 YEARS WARRANTY



Solida G2

111052	19 W	2261 lm	119 lm/W	625x80x55 mm	6 pcs
111058	30 W	3540 lm	118 lm/W	905x80x55 mm	6 pcs
111059	34 W	3978 lm	117 lm/W	905x80x55 mm	6 pcs
111061	33 W	3927 lm	119 lm/W	1185x80x55 mm	6 pcs
111062	40 W	4720 lm	118 lm/W	1185x80x55 mm	6 pcs
111063	40 W	4800 lm	120 lm/W	1465x80x55 mm	4 pcs
111064	44 W	5192 lm	118 lm/W	1465x80x55 mm	4 pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65 | DALI Option | 1-10V | Emergency unit

3000K 4000K 6500K

TSE EAC CE 5 YEARS WARRANTY




Inovaled G2

113454	19 W	2033lm	107lm/W	630x72x59 mm	6pcs
113457	26 W	2782lm	107lm/W	910x72x59 mm	6pcs
113460	34 W	3672lm	108lm/W	1190x72x59 mm	6pcs

Aluminium | LM80 TM21 | ENEC Driver | IP66 | DALI Option | Emergency unit


3000K 4000K 6500K



Adjustable Mounting Apparatus

EAC CE

Fontana
Waterproof Luminaires





Easy Mounting
Through Wiring
Easy Electrical Installation
IP65 Dust and Waterproof
IP66 Option



Fontana

111078	19 W	2261 lm	119 lm/W	625x80x78 mm	6pcs
111079	26 W	3120 lm	120 lm/W	905x80x78 mm	6pcs
111082	30 W	3540 lm	118 lm/W	905x80x78 mm	6pcs
111083	34 W	3944 lm	116 lm/W	905x80x78 mm	6pcs
111084	33 W	3993 lm	121 lm/W	1185x80x78 mm	6pcs
111085	40 W	4720 lm	118 lm/W	1185x80x78 mm	6pcs
111086	40 W	4720 lm	118 lm/W	1465x80x78 mm	4pcs
111087	44 W	5236 lm	119 lm/W	1465x80x78 mm	4pcs

PC | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65 | DALI Option | 1-10V | Emergency unit

3000K 4000K 6500K



Folta

115005	18 W	2142 lm	119 lm/W	555x64x46 mm	12pcs
115007	23 W	2806 lm	122 lm/W	805x64x46 mm	12pcs
115009	33 W	3993 lm	121 lm/W	1055x64x46 mm	12pcs
115011	43 W	5160 lm	120 lm/W	1305x64x46 mm	12pcs

PC | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65 | DALI Option | 1-10V | Emergency unit

3000K 4000K 6500K

Pelsan

MAX FAMILY
in Industrial Lighting





Fontana Max

114465	50 W	6500lm	130lm/W	78x80x1180 mm	6pcs
114467	75 W	9450lm	126lm/W	78x80x1180 mm	6pcs

PC | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65 | DALI Option | 1-10V | Emergency unit

3000K 4000K 6500K

TSE EAC CE



Largo Max

111114	50 W	6750lm	135lm/W	1273x85x125 mm	6pcs
111113	75 W	9600lm	128lm/W	1273x85x125 mm	6pcs

GRP | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65 | DALI Option | 1-10V | Emergency unit

3000K 4000K 6500K

TSE EAC CE



Inovaled Max

113643	100 W	12300lm	123lm/W	910x72x59 mm	6pcs
113644	120 W	15000lm	125lm/W	1190x72x59 mm	6pcs
113645	150 W	18750lm	125lm/W	1470x72x59 mm	6pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65 | DALI Option | 1-10V | Emergency unit


3000K 4000K 6500K

CE

24V DC


Engine Room


Harsh Environment


Shipyards


Building Site

24V DC



Largo

110119	21 W	1785 lm	85 lm/W	663x85x85 mm	6pcs
110114	42 W	3570 lm	85 lm/W	1273x85x85 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | SEMI OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K

CE

24V DC



Sterio

110171	50 W	5000 lm	100 lm/W	225x195x59 mm	6pcs
110506	100 W	10000 lm	100 lm/W	225x365x85 mm	4pcs

Aluminium injection | IK10 | IP66 | Anti Glare Diffuser

5700K

CE



Building Site



Power Plants



Hydraulic Power Plants

110V DC



Isoled

112976	36 W	3600 lm	100 lm/W	595x595x61 mm	6pcs
112988	36 W	3600 lm	100 lm/W	595x595x61 mm	6pcs

Metal | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP40

CE

110V DC



Largo

112974	36 W	3780 lm	105 lm/W	1273x85x85 mm	6pcs
112975	45 W	4725 lm	105 lm/W	1273x85x85 mm	6pcs
112989	55 W	5775 lm	105 lm/W	1273x85x85 mm	4pcs

GRP | OPAL Diffuser | CLEAR Diffuser | SEMI OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K

CE

110V DC



Ria Med G2

113936	80 W	10000 lm	125lm/W	340x274x66 mm	4pcs

Aluminium Injection | Tempered Glass | LM80 TM21 | ENEC Driver | IP66 | DALI Option

3000K 4000K 6500K

CE

Emergencies are under the assurance of Pelsan



- Adjustable Head
- Double Switch and Test Button
- Charge, Discharging Indicator
- 6 Hours Discharging Time
- Hangable / Portable Design
- IP40 / IP65 Options

Emergency Luminaires



2x5 / 2x10
Emergency Spot
IP40/IP65



Emergency
Latern



Exiled



Vialed



Ausled
IP65 Emergency





IP65 Emergency Spot

110679	2x10W	6 h	340x480x150 mm	1pcs

Metal | PMMA Lens | LM80 TM21 | ENEC Driver | IP65 | Emergency unit

3000K 4000K 6500K

Adjustable Head | Test Switch | Charge Indicator | Test Button





2x5W



2x10W

Metal Emergency Spot

109781	2x5W	6 h	275x340x80 mm	4pcs
109780	2x10W	6 h	325x340x80 mm	4pcs

Metal | PMMA Lens | LM80 TM21 | ENEC Driver | IP40 | Emergency unit

3000K 4000K 6500K

Adjustable Head | Test Switch | Charge Indicator | Test Button



2x3W



2x5W



2x10W

Emergency Spot


203911	2x3 W	4 h	261x89x59 mm	10pcs
203913	2x5 W	2 h	280x279x89 mm	8pcs
203907	2x10 W	6 h	286x299x89 mm	8pcs

Polymer Injection | CLEAR Diffuser | IP40

Adjustable Head | Test Switch | Charge Indicator | Test Button







Ausled IP65 Emergency

115140	3 W	3 h	350x117x76 mm	12pcs
108390	5 W	3 h	350x117x76 mm	12pcs
110667	10 W	3 h	350x117x76 mm	12pcs

Polymer Injection | CLEAR Diffuser | LM80 TM21 | ENEC Driver | IP65 | Emergency unit

3000K 4000K 6500K

Recessed/Surface Mounted | AC/DC Operating Mode



Lantern

204619	30 LED	3 W	8 h	203x55x29 mm	40pcs
204620	40/60LED	4/6 W	8 h	342x55x29 mm	24pcs
204623	90LED	9 W	8 h	482x55x29 mm	20pcs

Polymer Injection | CLEAR Diffuser | IP40

Replaceable Battery | Test Switch | Charge Indicator



Pendant



Recessed M.



Surface M.

Vialed


201165	Pendant	3 W	3 h	280x205x45 mm	10pcs
201013	Surface M.	3 W	3 h	280x205x45 mm	10pcs
201110	Recessed M.	3 W	3 h	310x205x110 mm	10pcs

Aluminium IP20

EAC CE

Single side-Double side | Charge Indicator | Label Options




4 Different Routing Labels

Rausled Surface Mounted

109387	3 W	3 h	350x217x117 mm	10pcs

Polymer Injection IP65

EAC CE



Recessed M.

Exiled Recessed Mounted

200545	Sıva Altı / Recessed M.	3 W	3 h	434x150x90 mm	10pcs

Aluminium IP20

EAC CE

Charge Indicator | Single side-Double side | Test Switch



Exiled


203891	E5 (single side)	3 W	3 h	360x150x24 mm	10pcs
203885	E5 (double side)	3 W	3 h	360x150x24 mm	10pcs
203890	E54	3 W	3 h	360x150x24 mm	10pcs
203887	E114-115	3 W	3 h	360x150x24 mm	10pcs
203888	E116	3 W	3 h	360x150x24 mm	10pcs
203889	E186	3 W	3 h	360x150x24 mm	10pcs

Aluminium IP20

EAC CE

Single side-Double side | Test Switch | Charge Indicator | Label Options

Label Options



different options
www.pelsan.com.tr



Piroliz Ex-Proof Canopy

111376	50 W	8250lm	165lm/W	395x395x132 mm	1pcs
111375	75 W	12000lm	160lm/W	395x395x132 mm	1pcs
111374	100 W	15500lm	155lm/W	395x395x132 mm	1pcs
111382	125 W	19000lm	152lm/W	395x395x132 mm	1pcs
111373	150 W	22500lm	150lm/W	395x395x132 mm	1pcs
111056	200 W	28600lm	143lm/W	395x395x132 mm	1pcs

Aluminium injection · Polymer Reflection · Tempered Glass · LM80 TM21 · ENEC Driver · IP66

CE Ex ZONE 2 ZONE 22 II 3G Ex nR IIC T5 Gc II 3D Ex tc IIIC T95° Dc



High Performance for Gas Station

- Up to 120lm/W Efficacy
- Aluminium Injection Body
- ENEC Certified Driver

Piroliz Canopy

106583	75 W	8625lm	115lm/W	395x385x132 mm	1pcs
106584	100 W	11000lm	110lm/W	395x385x132 mm	1pcs
106585	125 W	13125lm	105lm/W	395x385x132 mm	1pcs

Aluminium Injection · PMMA Lens · Tempered Glass · LM80 TM21 · ENEC Driver · IP65 · DALI Option

3000K 4000K 6500K

CE



80W 140lm/W

- Aluminium Body
- ENEC Certified Driver
- LM80-TM21 Reported LED Chips

Okta Canopy

106627	80 W	11200lm	140lm/W	400x400x140 mm	1pcs
110173	100 W	11000lm	110lm/W	400x400x140 mm	1pcs

Aluminium Injection · Tempered Glass · LM80 TM21 · ENEC Driver · IP65 · DALI Option

3000K 4000K 6500K

CE



Eco Solution for Gas Station

Lenta Canopy

110507	100 W	10000lm	100lm/W	400x400x88 mm	1pcs

Aluminium Injection · Tempered Glass · IP65

5000K

CE









Cronto IP66



5 YEARS WARRANTY

Specifications of IP67 Driver

ENEC Certified | 100.000 h Driver Lifetime | 10kV Internal SPD | -40°C +55°C | IP67 | 100-277Vac



Cronto **IP66** 150-200W

111333	150 W	22350 lm	149 lm/W	555x230x135 mm	1pcs
111334	200 W	28800 lm	144 lm/W	555x230x135 mm	1pcs

Aluminium Injection | Tempered Glass | LM80 TM21 | ENEC Driver | IP65 | DALI Option

1-10V | Emergency unit | 3000K | 4000K | 6500K

EAC CE 5 YEARS WARRANTY



Cronto **IP66** 250-300W

111331	250 W	36000 lm	144 lm/W	655x230x135 mm	1pcs
111332	300 W	42300 lm	141 lm/W	655x230x135 mm	1pcs

Aluminium Injection | Tempered Glass | LM80 TM21 | ENEC Driver | IP65 | DALI Option

1-10V | Emergency unit | 3000K | 4000K | 6500K

EAC CE 5 YEARS WARRANTY



Cronto **IP66** 350-400W

111335	350 W	48650 lm	139 lm/W	760x230x135 mm	1pcs
111336	400 W	54800 lm	137 lm/W	760x230x135 mm	1pcs

Aluminium Injection | Tempered Glass | LM80 TM21 | ENEC Driver | IP65 | DALI Option

1-10V | Emergency unit | 3000K | 4000K | 6500K

EAC CE 5 YEARS WARRANTY

5 YEARS WARRANTY



Factories & Warehouses Working 7/24

- 5 Years Warranty
- Aluminium Body
- +70.000 Hours Lifetime
- 4 kv Surge Protection
- Up to 134lm/W Efficacy

Etna G2

Narrow angle product codes.

111273	100W	13300lm	133lm/W	590x86x178 mm	1pcs
111271	150W	19950lm	133lm/W	870x86x178 mm	1pcs
111269	200W	26800lm	134lm/W	1150x86x178 mm	1pcs
111258	250W	33250lm	133lm/W	1430x86x178 mm	1pcs
111256	300W	38400lm	128lm/W	1430x86x178 mm	1pcs

Aluminium · Aluminium Reflector · Tempered Glass · LM80 TM21 · ENEC Driver · IP65 · 3000K · 4000K · 6500K

DALI Option · Emergency unit · Wide Angle · Narrow Angle · SENSOR Option · 1-10V

TSE EAC CE



Heavy Industrial Facilities Ta= +70°C

Etna G2 Heavy Industry

Narrow angle product codes.

113466	100W	13300lm	133lm/W	1200x86x178 mm	1pcs
113467	200W	26800lm	134lm/W	1500x86x178 mm	1pcs

Aluminium · Aluminium Reflector · Tempered Glass · LM80 TM21 · ENEC Driver · IP65 · 3000K · 4000K · 6500K

DALI Option · Emergency unit · Wide Angle · Narrow Angle · SENSOR Option · 1-10V

TSE EAC CE



Tempered Filmed Glass and Facilities

Etna G2 Food

Narrow angle product codes.

113336	100W	13300lm	133lm/W	590x86x178 mm	1pcs
113338	150W	19950lm	133lm/W	870x86x178 mm	1pcs
113340	200W	26800lm	134lm/W	1150x86x178 mm	1pcs
113342	250W	33250lm	133lm/W	1430x86x178 mm	1pcs
113344	300W	38400lm	128lm/W	1430x86x178 mm	1pcs

Aluminium · Aluminium Reflector · Tempered Glass · LM80 TM21 · ENEC Driver · IP65 · 3000K · 4000K · 6500K

DALI Option · Emergency unit · Wide Angle · Narrow Angle · SENSOR Option · 1-10V

TSE EAC CE



Frozen & Cold Warehouses Ta= -40°C

Etna G2 Frozen

Narrow angle product codes.

113337	100W	13300lm	133lm/W	590x86x178 mm	1pcs
113339	150W	19950lm	133lm/W	870x86x178 mm	1pcs
113341	200W	26800lm	134lm/W	1150x86x178 mm	1pcs
113343	250W	33250lm	133lm/W	1430x86x178 mm	1pcs
113345	300W	38400lm	128lm/W	1430x86x178 mm	1pcs

Aluminium · Aluminium Reflector · Tempered Glass · LM80 TM21 · ENEC Driver · IP65 · 3000K · 4000K · 6500K

DALI Option · Emergency unit · Wide Angle · Narrow Angle · SENSOR Option · 1-10V

TSE EAC CE

- IK10, High Impact Resistance
- Anti-Glare Design
- HD Broadcast
- Up to 150 lm/W
- Lens Options 30° 60° 90° asymmetric
- Casambi Option (Wireless Lighting Control System)



Flawless Lighting Experience with Neta, Especially for Professional Sport Fields



Neta 100W

110684 | 100 W | 15000lm | 150 lm/W | 1300x240x75 mm | 1pcs

Metal | LM80 TM21 | ENEC Driver | IP20 | DALI Option | Emergency unit | SENSOR Option

CASAMBI 3000K 4000K 6500K

IK10

EAC CE



Neta 150W

110685 | 150 W | 21750lm | 145 lm/W | 1300x240x75 mm | 1pcs

Metal | LM80 TM21 | ENEC Driver | IP20 | DALI Option | Emergency unit | SENSOR Option

CASAMBI 3000K 4000K 6500K

IK10

EAC CE



Neta 200W

110686 | 200 W | 28400lm | 142 lm/W | 1300x240x75 mm | 1pcs

Metal | LM80 TM21 | ENEC Driver | IP20 | DALI Option | Emergency unit | SENSOR Option

CASAMBI 3000K 4000K 6500K

IK10

EAC CE







Cost Effective!

- 5 Years Warranty
- +50.000 Hours Lifetime
- 125lm/W Efficacy
- Aluminium Body
- Easy Installation

Hima G2

114394	75 W	9075 lm	121lm/W	585x115x80 mm	1pcs
111072	75 W	9000 lm	120lm/W	865x115x80 mm	1pcs
111073	100 W	11500 lm	115lm/W	865x115x80 mm	1pcs
111066	150 W	17250 lm	115lm/W	1145x115x80 mm	1pcs

Aluminium · Aluminium Reflector · Tempered Glass · LM80 TM21 · ENEC Driver · IP65

DALI Option · Emergency unit · SENSOR Option · 3000K · 4000K · 6500K



Karpat G2

111105	75 W	8250lm	110lm/W	1200x110x60 mm	2pcs
111766	120 W	13200lm	110lm/W	1200x110x60 mm	2pcs
113479	150 W	19200lm	128lm/W	1500x110x60 mm	2pcs

Metal · Aluminium Reflector · Tempered Glass · Electronic Ballast · IP65 · Emergency unit



Sports Fields! IK10

- Anti-Glare Optic Design for Professional Sports Fields
- High Impact Resistance, IK10
- High Efficacy for More Energy Saving! 130 lm/W
- Wide Power Option 75-300W

Esta

109035	100 W	12960lm	129lm/W	1220x305x75 mm	1pcs
110728	150 W	18600lm	124lm/W	1220x305x75 mm	1pcs
109826	230 W	30360lm	132lm/W	1220x305x75 mm	1pcs

Metal · OPAL Diffuser · METAL Diffuser · LM80 TM21 · ENEC Driver · Class II · IP40 · DALI Option · Emergency unit

IK10 · LENS Option · CASAMBI · 3000K · 4000K · 6500K



5 YEARS WARRANTY

Anti-Glare Optic Diffuser

- Pendant Application with Chain
- Up to 154lm/W Efficacy
- Easy Installation

Castor G3

114042	75 W	11550lm	154lm/W	272x180 mm	6pcs
114043	100 W	14900lm	149lm/W	272x180 mm	6pcs
114044	150 W	21900lm	146lm/W	323x186 mm	4pcs
114045	200 W	28400lm	142lm/W	323x186 mm	4pcs

Aluminium Injection | Anti Glare Diffuser | IP65 | LM80 TM21 | DALI Option | Emergency unit | ENEC Driver | 4000K | 5700K | 6500K



Cost Effective

- Pendant Application with Chain
- +115lm/W Efficacy
- Easy Installation

Monte G2

110569	100 W	11500lm	115lm/W	272x180 mm	6pcs
110570	150 W	18450lm	123lm/W	323x186 mm	4pcs

Aluminium Injection | Tempered Glass | IP65 | 5700K

---

5 YEARS WARRANTY



140lm/W Efficacy!

Different Lens Angle



Sia

109221	150 W	21000lm	140lm/W	342x342x160 mm	1pcs
109554	200 W	25000lm	125lm/W	342x342x160 mm	1pcs


Aluminium injection | PMMA Lens | Tempered Glass | LM80 TM21 | ENEC Driver | IP65 | DALI Option | Emergency unit

3000K | 4000K | 6500K



140lm/W Efficacy!

Different Lens Angle




Sia **Heavy Industry**

110603	100 W	14500lm	145lm/W	342x342x123 mm	1pcs
110604	125 W	17500lm	140lm/W	342x342x123 mm	1pcs
110605	150 W	21300lm	142lm/W	342x342x123 mm	1pcs

Aluminium injection | PMMA Lens | Tempered Glass | LM80 TM21 | ENEC Driver | IP65 | DALI Option | Emergency unit

3000K | 4000K | 6500K

Ta=+70 °C



You can safely use Pelsan Ex-Proof Luminaires in chemical and paint facilities, oil storage facilities, oil filling and discharge facilities, ports & shipyards, power plants, industrial facilities and fuel stations!



LED Ex-Proof Waterproof

112894	22 W	6500K	2816 lm	128 lm/W	715x210x142 mm	1pcs
112896	44 W	6500K	5632 lm	128 lm/W	1310x210x142 mm	1pcs
112897	66 W	6500K	8448 lm	128 lm/W	1310x210x142 mm	1pcs

Aluminium | CLEAR PC | LM80 TM21 | ENEC Driver | IP66

3000K 4000K 6500K

Ex ZONE 1 ZONE 21

II 2G Ex db IIB T5 Gb
II 2D Ex tb IIIC T100°C Db



LED Ex-Proof Exit

112919	22 W	6500K	715x210x142 mm	1pcs

Aluminium | PC | LM80 TM21 | ENEC Driver | IP66

3000K 4000K 6500K

Ex ZONE 1 ZONE 21

II 2G Ex db IIB T5 Gb
II 2D Ex tb IIIC T100°C Db

Rausled Ex-Proof Emergency





ZONE 2 ZONE 22
II 3G Ex nR IIC T6 Gc
II 3D Ex tc IIIC T 85° Dc

Ausled Ex-Proof Emergency (3h)

109710	15 W	1500 lm	100lm/W	350x117x76 mm	6pcs

PC Body | CLEAR Diffuser | LM80 TM21 | ENEC Driver | IP65

Surface Mounted - Recessed Mounted



ZONE 2 ZONE 22
II 3G Ex nR IIC T6 Gc
II 3D Ex tc IIIC T 80° Dc

Largo LED Ex-Proof Emergency (3h)

111416	25 W	2750 lm	110lm/W	670x85x125 mm	6pcs
113055	45 W	4950 lm	110lm/W	1280x85x125 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K




ZONE 2 ZONE 22
II 3G Ex nR IIC T6 Gc
II 3D Ex tc IIIC T 80° Dc

Largo LED Ex-Proof Waterproof

108458	25 W	2750 lm	110lm/W	670x85x125 mm	6pcs
108459	45 W	4950 lm	110lm/W	1280x85x125 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K




ZONE 2 ZONE 22
II 3G Ex nR IIC T6 Gc
II 3D Ex tc IIIC T 80° Dc

Largo LED Tube Ex-Proof Waterproof

111402	1xG13	670x85x125 mm	6pcs
111404	2xG13	670x85x125 mm	6pcs
111405	1xG13	1280x85x125 mm	6pcs
111406	2xG13	1280x85x125 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K



ZONE 2 ZONE 22
II 3G Ex nR IIC T6 Gc
II 3D Ex tc IIIC T 80° Dc

Largo T8 Ex-Proof Waterproof

108297	2x18 W	–	G13 TL-D	670x85x125 mm	6pcs
108298	2x36 W	–	G13 TL-D	1280x85x125 mm	6pcs

GRP | OPAL Diffuser | CLEAR Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K



Elit Lirad Ex-Proof Floodlight

109707	50 W	7000lm	140lm/W	200x295x175 mm	6pcs

GRP | Aluminium Reflector | Tempered Glass | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K

ZONE 2 ZONE 22

II 3G Ex ec IIC T5 Gc
II 3D Ex tc IIIC (T95°C) DC



Nairo Ex-Proof Floodlight

111372	50 W	8250lm	165lm/W	342x342x121 mm	1pcs
111371	75 W	12000lm	160lm/W	342x342x121 mm	1pcs
111370	100 W	15500lm	155lm/W	342x342x121 mm	1pcs
111369	125 W	19000lm	152lm/W	342x342x121 mm	1pcs
111368	150 W	22500lm	150lm/W	342x342x121 mm	1pcs
111055	200 W	28600lm	143lm/W	342x342x121 mm	1pcs

Aluminium injection | PMMA Lens | Tempered Glass | LM80 TM21 | ENEC Driver | IP66

3000K 4000K 6500K

ZONE 2 ZONE 22

II 3G Ex ec IIC T5 Gc
II 3D Ex tc IIIC (T95°C) DC



Sia Ex-Proof Highbay

111381	50 W	8250lm	165lm/W	342x342x160 mm	1pcs
111380	75 W	12000lm	160lm/W	342x342x160 mm	1pcs
111379	100 W	15500lm	155lm/W	342x342x160 mm	1pcs
111378	125 W	19000lm	152lm/W	342x342x160 mm	1pcs
111377	150 W	22500lm	150lm/W	342x342x160 mm	1pcs
111053	200 W	28600lm	143lm/W	342x342x160 mm	1pcs

Aluminium injection | PMMA Lens | Tempered Glass | LM80 TM21 | ENEC Driver | IP66

3000K 4000K 6500K

ZONE 2 ZONE 22

II 3G Ex ec IIC T5 Gc
II 3D Ex tc IIIC (T95°C) DC



Piroliz Ex-Proof Canopy

111376	50 W	8250lm	165lm/W	395x395x132 mm	1pcs
111375	75 W	12000lm	160lm/W	395x395x132 mm	1pcs
111374	100 W	15500lm	155lm/W	395x395x132 mm	1pcs
111382	125 W	19000lm	152lm/W	395x395x132 mm	1pcs
111373	150 W	22500lm	150lm/W	395x395x132 mm	1pcs
110056	200 W	28600lm	143lm/W	395x395x132 mm	1pcs

Aluminium injection | PMMA Lens | Tempered Glass | LM80 TM21 | ENEC Driver | IP66

3000K 4000K 6500K

ZONE 2 ZONE 22

II 3G Ex ec IIC T5 Gc
II 3D Ex tc IIIC (T95°C) DC



Nairo Ex-Proof Street

111367	50 W	8100lm	162lm/W	485x152x352 mm	1pcs
111366	75 W	11775lm	157lm/W	485x152x352 mm	1pcs
111365	100 W	15200lm	152lm/W	485x152x352 mm	1pcs
111364	125 W	18625lm	149lm/W	485x152x352 mm	1pcs
111363	150 W	21900lm	146lm/W	485x152x352 mm	1pcs
111362	200 W	28000lm	140lm/W	485x152x352 mm	1pcs

Aluminium injection | PMMA Lens | Tempered Glass | LM80 TM21 | ENEC Driver | IP66

3000K 4000K 6500K

ZONE 2 ZONE 22

II 3G Ex ec IIC T5 Gc
II 3D Ex tc IIIC (T95°C) DC

Cruzo IP66

1200W
LED Floodlight

product video








CB, ENEC Certified


Lens Options



Specifications of IP67 Driver

- ENEC Certified
- 100.000 h Driver Lifetime
- 10kV Internal SPD
- -40°C +55°C
- IP67
- 100-277Vac





Cruzo **IP66** 300-500W

110791	300 W	42300 lm	141 lm/W	677x377x226 mm	1pcs
110792	400 W	58000 lm	145 lm/W	577x613x294 mm	1pcs
110793	500 W	71000 lm	142 lm/W	577x613x294 mm	1pcs

Aluminium injection | IP66 | Tempered Glass | LM80 TM21 | ENEC Driver

3000K 4000K 5700K 6500K 2-Step DIM

CB EAC



Cruzo **IP66** 600-800W

110794	600 W	84600 lm	141 lm/W	677x613x294 mm	1pcs
110795	800 W	115200 lm	144 lm/W	677x824x345 mm	1pcs

Aluminium injection | IP66 | Tempered Glass | LM80 TM21 | ENEC Driver

3000K 4000K 5700K 6500K 2-Step DIM

CB EAC



Cruzo **IP66** 1000-1200W

110796	900 W	126900 lm	141 lm/W	677x824x345 mm	1pcs
110797	1000 W	139000 lm	139 lm/W	677x824x345 mm	1pcs
110798	1200 W	157000 lm	130 lm/W	712x1105x147 mm	1pcs

Aluminium injection | IP66 | Tempered Glass | LM80 TM21 | ENEC Driver

3000K 4000K 5700K 6500K 2-Step DIM

CB EAC



Ria Lens 400W



Ria Med G2




Ria **IP66**
Aluminium Reflector

Specifications of IP67 Driver

ENEC Certified | 100.000 h Driver Lifetime | 10kV Internal SPD | -40°C +55°C | IP67 | 100-277 Vac



Suitable for highest pole!



Ria **IP66** Symmetric

107140	180 W	23580 lm	131lm/W	400x418x100 mm	1pcs
107141	200 W	24800 lm	124lm/W	400x418x100 mm	1pcs
107130	240 W	28800 lm	120lm/W	400x418x100 mm	1pcs
109218	300 W	37200 lm	124lm/W	400x418x100 mm	1pcs


Aluminium Injection | Aluminium Reflector | Tempered Glass | LM80 TM21 | ENEC Driver | IP66

3000K 4000K 6500K 2-Step DIM

Symmetric Light Distrubition







Ria **IP66** Asymmetric

107137	180 W	23580 lm	131lm/W	400x418x100 mm	1pcs
107138	200 W	24800 lm	124lm/W	400x418x100 mm	1pcs
107127	240 W	28800 lm	120lm/W	400x418x100 mm	1pcs

Aluminium Injection | Aluminium Reflector | Tempered Glass | LM80 TM21 | ENEC Driver | IP66


3000K 4000K 6500K 2-Step DIM

Asymmetric Light Distrubition





Suitable for widest areas



Ria **IP66**


107121	100 W	11000 lm	110lm/W	400x418x100 mm	1pcs
107124	150 W	15000 lm	100lm/W	400x418x100 mm	1pcs

Aluminium Injection | Aluminium Reflector | Tempered Glass | LM80 TM21 | ENEC Driver | IP66 | DALI Option

3000K 4000K 6500K 2-Step DIM







Ria Lens Symmetric

110356	200 W	30800 lm	154lm/W	400x418x100 mm	1pcs
110355	250 W	36500 lm	146lm/W	400x418x100 mm	1pcs
110354	300 W	40500 lm	135lm/W	400x418x100 mm	1pcs
115039	400 W	56000 lm	140lm/W	400x418x100 mm	1pcs

Aluminium Injection | Tempered Glass | LM80 TM21 | ENEC Driver | IP66 | DALI Option

3000K 4000K 6500K 2-Step DIM 1-10V

Symmetric Light Distrubition





Ria Lens Asymmetric

110770	200 W	30800 lm	154lm/W	400x418x100 mm	1pcs
110771	250 W	36500 lm	146lm/W	400x418x100 mm	1pcs
110772	300 W	40500 lm	135lm/W	400x418x100 mm	1pcs

Aluminium Injection | Tempered Glass | LM80 TM21 | ENEC Driver | IP66 | DALI Option

3000K 4000K 6500K 2-Step DIM 1-10V

Asymmetric Light Distrubition






Ria Tunnel

110443	200 W	28800 lm	144lm/W	400x418x100 mm	1pcs
110444	250 W	34750 lm	139lm/W	400x418x100 mm	1pcs
110445	300 W	40500 lm	135lm/W	400x418x100 mm	1pcs

Aluminium Injection | Tempered Glass | LM80 TM21 | ENEC Driver | IP66 | DALI Option

3000K 4000K 6500K 2-Step DIM 1-10V





Ria Med G2

111788	60 W	8820 lm	147lm/W	340x274x66 mm	4pcs
111785	80 W	11360 lm	142lm/W	340x274x66 mm	4pcs
111660	100 W	13800 lm	138lm/W	340x274x66 mm	4pcs
111666	150 W	19050 lm	127lm/W	340x274x66 mm	4pcs

Aluminium Injection | Tempered Glass | LM80 TM21 | ENEC Driver | IP66 | DALI Option

3000K 4000K 6500K 2-Step DIM 1-10V

Pelsan

STERIO IP66

Modular Floodlight

Aluminium Injection Body

IP66, Dust and Waterproof

IK10 Body



MODULAR



Sterio **IP66** 50-100W

109787	50 W	5000 lm	100lm/W	225x195x59 mm	6pcs
109666	100 W	10000 lm	100lm/W	225x365x85 mm	4pcs

Aluminium injection | IK10 | IP66 | Anti Glare Diffuser

5700K

EAC CE



Sterio **IP66** 200-300W

109536	200 W	20000 lm	100lm/W	415x360x85 mm	1pcs
109537	300 W	30000 lm	100lm/W	415x540x85 mm	1pcs

Aluminium injection | IK10 | IP66 | Anti Glare Diffuser

5700K

EAC CE



Sterio **IP66** 450W

109538	450 W	40500 lm	100lm/W	795x390x85 mm	1pcs

Aluminium injection | IK10 | IP66 | Anti Glare Diffuser

5700K

EAC CE

Lecto

- 50W / 100W / 150W / 200W / 300W
- +100lm/W
- Aluminium Injection Body
- Metal Cable Glant
- Rotary Console, Easy Installation
- Air Plug, Maisture Proof





Lecto 50W / 100W

109304	50 W	5000lm	100lm/W	245x190x33 mm	6pcs
109305	100 W	10000lm	100lm/W	320x268x33 mm	4pcs

Aluminium injection | Reflector | Tempered Glass | IP65

5000K



Lecto 150W

109306	150 W	15000lm	100lm/W	348x256x33 mm	6pcs

Aluminium injection | Reflector | Tempered Glass | IP65

5000K



Lecto 200W

111284	200 W	19000lm	95lm/W	420x320x35 mm	4pcs

Aluminium injection | Reflector | Tempered Glass | IP65

5000K

New



Lecto 300W

114120	300 W	30000lm	100lm/W	470x335x45 mm	4pcs

Aluminium injection | Reflector | Tempered Glass | IP65

5000K

Pelsan

Up to 165lm/W



Rio Xs **IP66**


- 50W / 60W / 80W / 100W
- Aluminium Injection Body, IK09
- IP66, Dust and Waterproof
- IP67, ENEC Certified Driver
- LED Chips Lifetime +100.000 hrs L70@Ts=85°C
- IK08 Tempered Glass
- Tool Free



Tool Free Design



Adjustable Angle





Rio Xs **G2 IP66**

110975	PLSHA	50 W	7750lm	155lm/W	232x567x106 mm	1pcs
110974	PLSHA	60 W	9900lm	165lm/W	232x567x106 mm	1pcs
110973	PLSHA	80 W	11400lm	143lm/W	232x567x106 mm	1pcs
110972	PLSHA	100 W	15000lm	150lm/W	232x567x106 mm	1pcs

Aluminium injection · PMMA Lens · Tempered Glass · LM80 TM21 · ENEC Driver · IP66 · IK09

3000K · 4000K · 6500K

Rio **IP66**

- Up to 163lm/W Efficacy
- LED Chip: 100.000 Hours Lifetime
- ENEC Certified LED Driver
- LED Driver: 100.000h Lifetime
- Surge Protection, 10 kV
- Aluminium Injection Body
- 5 Different Console Angles
- Road Lighting Class ME1-ME6



Rio S G2 **IP66**



109169	PLSHA	80 W	13040 lm	163lm/W	476x280x110 mm	1pcs
109171	PLSHA	100 W	15000 lm	150lm/W	476x280x110 mm	1pcs
109173	PLSHA	125 W	18375 lm	147lm/W	476x280x110 mm	1pcs
116120	PLSHA	140 W	20300 lm	145lm/W	476x280x110 mm	1pcs
109175	PLSHA	150 W	21450 lm	143lm/W	476x280x110 mm	1pcs

Aluminium injection · PMMA Lens · Tempered Glass · LM80 TM21 · ENEC Driver · IP66 · IK10

3000K 4000K 6500K

Rio M G2 **IP66**



115166	180 W	28800lm	160lm/W	616x330x1 mm	1pcs	
115167	200 W	31600lm	158lm/W	616x330x1 mm	1pcs	

Aluminium injection · PMMA Lens · Tempered Glass · LM80 TM21 · ENEC Driver · IP66 · IK10

3000K 4000K 6500K

Rio L **IP66**



110784	240 W	34800lm	145lm/W	727x370x131 mm	1pcs	
110785	270 W	38610lm	143lm/W	727x370x131 mm	1pcs	
110786	300 W	42000lm	140lm/W	727x370x131 mm	1pcs	

Aluminium injection · PMMA Lens · Tempered Glass · LM80 TM21 · ENEC Driver · IP66 · IK10

3000K 4000K 6500K



Doka G2

111793	60 W	8820 lm	147lm/W	362x263x65 mm	4pcs
111795	80 W	11360 lm	142lm/W	362x263x65 mm	4pcs
111797	100 W	13800 lm	138lm/W	362x263x65 mm	4pcs
111799	150 W	19050 lm	127lm/W	362x263x65 mm	4pcs

Aluminium injection · PMMA Lens · Tempered Glass · LM80 TM21 · ENEC Driver · IP66 · IK08

3000K · 4000K · 6500K

TSE · EAC · CE · 5 YEARS WARRANTY



60W - 80W

100W



150W

Berlin

113622	60 W	6600lm	110lm/W	409x165x54 mm	10pcs
114994	80 W	8400lm	105lm/W	409x165x54 mm	10pcs
113623	100 W	10500lm	110lm/W	498x201x73 mm	6pcs
109856	150 W	15750lm	105lm/W	571x248x76 mm	6pcs

Aluminium injection · PC Diffuser · IP65

4000K

EAC · CE

Video





up to 146lm/W

Photocell

Madrid

109841	20 W	2760lm	138lm/W	324x201x75 mm	6pcs
108494	33 W	4257lm	129lm/W	324x201x75 mm	6pcs
109877	40 W	5840lm	146lm/W	324x201x75 mm	6pcs

Polymer Injection · PC Diffuser · LM80 TM21 · ENEC Driver · IP65

4000K · 6500K

EAC · CE



Photocell

Seul

105979 | 30 W | 2720lm | 90lm/W | 425x240x170x240 mm | 10pcs

Polymer Inj. Body · PC Reflector · PC Diffuser · LM80 TM21 · ENEC Driver · IP65

4000K · 6500K

EAC · CE

Accra Solar



All In One

1. No line voltage and cabling
2. No mountly electric bills
3. All in one solution
4. Remote Control











CE







Accra Solar HLO

209010	800lm	450x210x80 mm	4pcs
280644	1200lm	450x210x80 mm	4pcs


ABS | IP65 | 6500K

Mono Crystal Panel
LifePO4 Battery
3day autonomus time

Photocell
Motion Sensor



CE



Remote Control

1. **Mod 1:** Motion Sensor
2. **Mod 2:** Low light + Motion sensor
3. **Mod 3:** On/ Off
4. **Mod 4:** Time adjustable / Constant light

Accra Solar

109431	40 W	950lm	487x236x65 mm	6pcs
109432	60 W	1150lm	649x236x65 mm	6pcs

ABS | IP65

Photocell
Motion Sensor

LifePO4 Battery
2day autonomus time

6500K



CE

Remote Control

1. **Mod 1:** On/ Off
2. **Mod 2:** Low I high + Motion sensor
3. **Mod 3:** Time adjustable / Constant light

Accra Solar Floodlights


114064	50 W	355lm	205x158x46 mm	1pcs
114065	100 W	820lm	270x225x70 mm	1pcs

ABS | IP65

Photocell
LifePO4 Battery
2day autonomus time

6500K






Rio Xs G2 Solar

114957	20W	2500lm	567x232x106 mm	1pcs
114958	40W	5000lm	567x232x106 mm	1pcs
114981	60W	7500lm	567x232x106 mm	1pcs
114960	80W	10000lm	567x232x106 mm	1pcs
114961	100W	12500lm	567x232x106 mm	1pcs






Doka G2 Solar


114962	20W	2600lm	340x274x66 mm	1pcs
114963	40W	5200lm	340x274x66 mm	1pcs
114964	60W	7800lm	340x274x66 mm	1pcs
114965	80W	10400lm	340x274x66 mm	1pcs
114966	100W	12000lm	340x274x66 mm	1pcs





Madrid Solar

114991	20W	2600lm	324x201x75 mm	1pcs
114993	40W	4800lm	324x201x75 mm	1pcs



Solar Luminaire Pole


208468	Ø42mm 4m Pole	RAL7043	1pcs
208469	Ø60mm 4m Pole	RAL7043	1pcs
208474	Ø42mm 6m Pole	RAL7043	1pcs
208475	Ø60mm 6m Pole	RAL7043	1pcs
208476	Ø42mm 8m Pole	RAL7043	1pcs
208477	Ø60mm 8m Pole	RAL7043	1pcs














Olimpos

107509	50 W	5850lm	117lm/W	1pcs	
108846	50+25 W	8775lm	117lm/W	1pcs	

108498	50+50 W	11700lm	117lm/W	1pcs


108261	50 W	5850lm	117lm/W	1pcs	
108499	50+25 W	8775lm	117lm/W	1pcs	

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP65 | 3000K | 4000K | 6500K

CE







Olimpos Med

206073	Pole	1x30 W	3300lm	110lm/W	1pcs	206074	Bollard	14 W	1484lm	106lm/W	1pcs
206072	Pole	2x30 W	6600lm	110lm/W	1pcs	206075	Bollard	18 W	1944m	108lm/W	1pcs

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP65 | 3000K | 4000K | 6500K


CE

Mesaled



- 60W
- 5280lm
- Aluminium Body
- Anti-Glare Special Difusser

Anti-Glare Diffuser




Anti-glare special diffuser

- **Prismatic diffuser**
- **Anti-glare optic**
- **High tranmission diffuser**

RAL Code Options





Mesaled

108609	30 W	2700lm	90lm/W	3500x650x200 mm	1pcs
108608	60 W	5280lm	88lm/W	3500x650x200 mm	1pcs

Aluminium | Anti Glare Diffuser | LM80 TM21 | ENEC Driver | IP54

3000K 4000K 6500K


CE

Pelsan

Limra




- Aluminium Body
- Opal Diffuser
- Aluminium Reflector



RAL Code Options





Limra

108606	38 W	2090lm	55lm/W	4500x700 mm	1pcs
108605	80 W	4400lm	55lm/W	4500x700 mm	1pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP54


3000K 4000K 6500K


CE














Troya G2

206776	25 W	1575lm	63lm/W	600x450 mm	1pcs
206780	50 W	3150lm	63lm/W	600x450 mm	1pcs
206783	75 W	4725lm	63lm/W	600x450 mm	1pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K

Karya

206804	25 W	2800lm	112lm/W	330x330x747 mm	1pcs
206807	50 W	5450lm	109lm/W	330x330x747 mm	1pcs
206810	75 W	7875lm	105lm/W	330x330x747 mm	1pcs

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K


Knidos

206786	25 W	2250lm	90lm/W	435x435x515 mm	1pcs
206789	50 W	4500lm	90lm/W	435x435x515 mm	1pcs
206792	75 W	6750lm	90lm/W	435x435x515 mm	1pcs

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP54

3000K 4000K 6500K

CE




Parion

206813	25 W	2575lm	103lm/W	500x500 mm	1pcs
206816	50 W	5150lm	103lm/W	500x500 mm	1pcs
206819	75 W	7725lm	103lm/W	500x500 mm	1pcs

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K




Eva

108610	40 W	3280lm	82lm/W	3500x520x200 mm	1pcs

Aluminium | Aluminium Reflector | CLEAR Diffuser | LM80 TM21 | ENEC Driver

3000K 4000K 6500K | IP54




Sardes

206795	25 W	2625lm	105lm/W	570x500 mm	1pcs
206798	50 W	5100lm	102lm/W	570x500 mm	1pcs
206801	75 W	7350lm	98lm/W	570x500 mm	1pcs

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K




Ruso

107461	E27	3000x550x230 mm	1pcs
107463	2xE27	3000x550x230 mm	1pcs

Aluminium | IP54

Color Option
RAL7043
RAL9005



Antalya

107531	E27	4500x540x250 mm	1pcs
107532	2xE27	4500x540x250 mm	1pcs

Aluminium | IP54

Color Option
RAL7043
RAL9005




Pedesa

107530	3xE27	3000x1180x200 mm	1pcs

IP54

Color Option
RAL7043
RAL9005

CE




Luzon

109736	40 W	4000lm	100lm/W	2500x120x220 mm	1pcs

Aluminium | Aluminium Reflector | CLEAR Diffuser | LM80 TM21 | ENEC Driver

3000K 4000K 6500K IP54




Alinda

107467	35 W	2450lm	90lm/W	2500x120x220 mm	1pcs

Aluminium | CLEAR Diffuser | LM80 TM21 | ENEC Driver

3000K 4000K 6500K IP54




Milas

108500	100 W	2000lm	2500x120x220 mm	1pcs

Aluminium | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP54

3000K 4000K 6500K




Datça

107628	30+40 W	2600+1200lm	87+30lm/W	3700x710 mm	1pcs
107619	150 W	12900lm	86lm/W	3700x710 mm	1pcs

Metal | Aluminium Reflector | OPAL Diffuser | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K




Samos

108612	150 W	26001m	52lm/W	4500x710 mm	1pcs
108163	50 W	2600lm	52lm/W	4500x710 mm	1pcs

Metal | Aluminium Reflector | OPAL Diffuser | LM80 TM21 | ENEC Driver

3000K 4000K 6500K IP65




Petra

107882	50 W	4500lm	100lm/W	4500x500x200 mm	1pcs

Aluminium | CLEAR Diffuser | LM80 TM21 | ENEC Driver

3000K 4000K 6500K IP65


CE



201197	3 m	Stepped Pipe Pole	1pcs
202678	3 m	1 Projector Pipe Mast	1pcs
201208	4 m	Stepped Pipe Pole	1pcs

202680	4 m	2 Projector Mast	1pcs
201201	4,5m	Lamp post	1pcs
202686	6 m	Lamp post	1pcs

202672	6 m	Stepped Pipe Pole	1pcs
202682	6 m	4 Projector Mast	1pcs
312688	Ankaraj	250mm Polyester	1pcs



202684	3 m	Street Pole	1pcs
202675	3 m	Camera Pole	1pcs
202685	3,5 m	Street Lamp Post	1pcs

202673	4,5 m	1 x Armature Pole	1pcs
312688	Ankraj	250mm Polyester	1pcs
202674	6 m	2 x Armature	1pcs

202670	6 m	Double Armature Pole	1pcs
202671	6 m	2xConsole Pole	1pcs
202668	6 m	Armature Pole	1pcs
312688	Ankraj	250mm Polyester	1pcs



Luzon2

110753 | 14 W | 1190lm | 85lm/W | 655x120x120 mm | 1pcs

Aluminium | LM80 TM21 | ENEC Driver | IP54

Color Option
RAL7043
RAL9005



Bali

108870 | 18 W | 2304lm | 128lm/W | 750x200x60x120 mm | 1pcs

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP65

3000K 4000K 6500K

CE



Bali

108870 | 18 W | 2304lm | 1pcs

Aluminium | ENEC Driver | IP65

3000K 4000K 6500K

Malta

108871 | 2x18 W | 4608lm | 1pcs

Aluminium | ENEC Driver | IP65

3000K 4000K 6500K

Maldiv

108872 | 18 W | 2304lm | 1pcs

Aluminium | ENEC Driver | IP65

3000K 4000K 6500K

Santorini

108873 | 2x18 W | 4608lm | 1pcs

Aluminium | ENEC Driver | IP65

3000K 4000K 6500K



Pega

108878 | 18 W | 1962lm | 1pcs

Aluminium | ENEC Driver | IP54

3000K 4000K 6500K

Mayorka

111419 | 18 W | 1280lm | 1pcs

Aluminium | ENEC Driver | IP65

3000K 4000K 6500K

Alinda

108859 | 18 W | 2052lm | 1pcs

Aluminium | ENEC Driver | IP54

3000K 4000K 6500K

Luzon

109027 | 20 W | 2000lm | 1pcs

Aluminium | ENEC Driver | IP54

3000K 4000K 6500K

CE





Alinda

109401-Alinda | 15 W | 1710lm | 114lm/W | 320x180x180 mm | 8pcs

Aluminium | ENEC Driver | IP54

3000K 4000K 6500K





Pega

109403 | 15 W | 1635lm | 109lm/W | 200x310x200 mm | 2pcs

Aluminium | IP54





Luzon

109402-Luzon | 15 W | 1500lm | 100lm/W | 310x230x230 mm | 1pcs

Aluminium | IP54 | IP65 | ENEC Driver

3000K 4000K 6500K






Tino

109404 | 1xE27 | - | - | 170x310x170 mm | 8pcs

Aluminium | IP54

CE






Işılay 1

110742 | E27 | 120x180x195 mm | 6pcs

Aluminium IP54






Işılay 2

110743 | 2xE27 | 120x300x195 mm | 6pcs

Aluminium IP54






Tibat 1

110744 | E27 | 198x180x120 mm | 6pcs

Aluminium IP54





Tibat 2

110745 | 2xE27 | 198x305x120 mm | 6pcs


Aluminium IP54

CE

Erbaled

109359	10 W	900lm	90lm/W	70x90x200 mm	8pcs
205288	Stud Bracket 21cm				10pcs


GRP | Clear Glass | LM80 TM21 | ENEC Driver | IP65



Erbaled

109486	10 W Amber	400lm	40lm/W	70x90x200 mm	8pcs
109485	10 W Green	400lm	40lm/W	70x90x200 mm	8pcs
205288	Stud Bracket 21cm				10pcs


GRP | Clear Glass | LM80 TM21 | ENEC Driver | IP65



Erbaled

110818	10 W Blue	400lm	40lm/W	70x90x200 mm	8pcs
109550	10 W Red	400lm	40lm/W	70x90x200 mm	8pcs
205288	Stud Bracket 21cm				10pcs

GRP | Clear Glass | LM80 TM21 | ENEC Driver | IP65



Santa

206822	15 W	2100lm	140lm/W	283x185x101 mm	1pcs
206825	25 W	3500lm	140lm/W	283x185x101 mm	1pcs
206828	37 W	5180lm	140lm/W	283x185x101 mm	1pcs

Aluminium | Clear Glass | LM80 TM21 | ENEC Driver | IP65



CE

Pelsan

Inovaled G2



Air Ventilated

Gland Keeping
Out The
Moisture

IP66
Dust and Waterproof

IK08

Tempered Glass

Aluminium Body



Inovaled G2 35cm

113292 | 14 W | 45+20° | 1540lm | 110lm/W | 350x72x59 mm | 4pcs

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP66

Color Options

AMBER | GREEN | RED | BLUE | 3000K | 4000K | 6500K

Different Lens Angle





Inovaled G2 65cm

113320 | 28 W | 45+20° | 3080lm | 110lm/W | 650x72x59 mm | 4pcs

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP66

Color Options

AMBER | GREEN | RED | BLUE | 3000K | 4000K | 6500K

Different Lens Angle





Inovaled G2 95cm

113328 | 42 W | 45+20° | 4620lm | 110lm/W | 945x72x59 mm | 4pcs

Aluminium | PMMA Lens | LM80 TM21 | ENEC Driver | IP66


Color Options

AMBER | GREEN | RED | BLUE | 3000K | 4000K | 6500K

Different Lens Angle



CE



LED Tube

314663	9 W	G13	950 lm	105lm/W	602x26 mm	25pcs
314664	9 W	G13	950 lm	105lm/W	602x26 mm	25pcs
314665	18 W	G13	1900 lm	100lm/W	1214x26 mm	25pcs
314666	18 W	G13	1900 lm	105lm/W	1214x26 mm	25pcs
314668	22 W	G13	2220 lm	101lm/W	1510x26 mm	25pcs
314669	22 W	G13	2220 lm	101lm/W	1510x26 mm	25pcs

Glass | A+ | 180° | CRI>80 | 30000h | 20000 | Single Side




Pro LED Tube

323524	22 W	6500K	G13	2970 lm	135lm/W	1510x26 mm	25pcs

Glass | A+ | 180° | CRI>80 | 30000h | 20000 | Single Side






Emergency LED Tube (1,5h)

315116	18 W	6500K	G13	1450 lm	80lm/W	1214x26 mm	25pcs

Glass | A+ | 180° | CRI>80 | 30000h | 20000 | Double Side





LED Tube with Sensor

315114	18 W	6500K	G13	1830 lm	101lm/W	1212x26 mm	25pcs
315115	18 W	6500K	G13	1500 lm	83lm/W	1212x26 mm	25pcs

Glass | A+ | 180° | CRI>80 | 30000h | 20000 | Double Side

CE

ATEX Certificate









Turkish Accreditation Certificate



TÜRK AKREDİTASYON KURUMU

AKREDİTASYON SERTİFİKASI

Deney Laboratuvarı olarak faaliyet gösteren,

PELSAN AYDINLATMA SANAYİ VE TİCARET A.Ş. Pelsan Aydınlatma Laboratuvarı

Çerkeşli OSB İmes 8.Cadde 400 Ada 6 Parsel Dış Kapı No:12 Dilovası KOCAELİ / TÜRKİYE

TÜRKAK tarafından yapılan denetim sonucunda TS EN ISO/IEC 17025:2017 Standardına göre Ek'te yer alan kapsamlarda akredite edilmiştir.

Akreditasyon No : **AB-0796-T**

Akreditasyon Tarihi : **28 Nisan 2015**

Revizyon Tarihi / No : **27 Ağustos 2019 / 04**

Bu Sertifika, yukarıda açık adı ve adresi yazılı Kuruluşun TS EN ISO/IEC 17025:2017 Standardına, ilgili Yönetmelik ve Tebliğlere uygunluğunu sürdürmesi halinde **26 Ağustos 2023** tarihine kadar geçerlidir.

Orbay EVRENSEVDİ
Genel Sekreter V.

Türk Akreditasyon Kurumu (TÜRKAK) ISO/IEC 17025 alanında Avrupa Akreditasyon Birliği (EA) ve Uluslararası Laboratuvar Akreditasyon Birliği (ILAC) ile çok taraflı anlaşma (MLA/MRA) imzalamıştır.

TSE Certificate



Road and Street Luminaires



Floodlight



General Purpose Fixed Luminaires



Recessed Mounted Office Luminaires

CB Certificate



Road and Street CB



Floodlight CB



Cruzo CB

ENEC Certificate



Road and Street ENEC



Floodlight ENEC

EAC Certificate



Office Luminaires



Downlights



Emergency Luminaires



Emergency Lighting and Monitoring Luminaires



Waterproof Luminaires



Highbay Luminaires



Floodlights



Road and Street


New
Architectural Lighting
Brand
recta
art and light
www.rectalighting.com

Pelsan



All your lighting needs in one adress.
Tüm aydınlatma ihtiyaçlarınız için tek adres.

www.**pelsan**.com.tr
info@pelsan.com.tr | export@pelsan.com.tr

HEAD OFFICE
GENEL MERKEZ
Çerkeşli O.S.B.
İmes 5. Cadde No:12
Dilovası / Kocaeli - TÜRKİYE

T : +9(0850) 460 75 76
F : +9(0216) 364 60 15

/PelsanAydinlatma
pelsan-aydinlatma
pelsan aydınlatma
/pelsanaydinlatma
/PelsanLight